

AERIAL FIREFIGHTING CONFERENCE



Guardian Mobility will be attending:

Contact me if you wish to meet up: Giles Peeters - cell: +1-613-614-6911 gpeeters@guardianmobility.com/

Please check out our website: https://www.guardianmobility.com/

GUARDIAN MOBILITY - IRIDIUM CERTUS® 100

Guardian is investing into Iridium Certus® 100 to become the world leader in providing midband satellite end-to-end aviation solutions.

To achieve this there has been significant investment in hardware, networks, gateway/billing services and airtime licenses to offer unique services within the aviator sector. After 2 years of development, services will soon (Q2 2022) be available with features and capability as follows:

- Bi-directional 88/88 kbps background IP
- Integrate with cellular and backup Iridium Short Burst Data (SBD)
 - FAA & Iridium certified
 - Automated Flight Following (AFF)
 - Aerial Firefighting bucket drop information
 - Live video streaming and imagery
 - Satellite voice
 - VOIP
 - Flight Data Monitoring (FDM)
 - Integration to loadcells and onboard CPU's
 - Gateway services for 3rd party devices into AFF gateway.

Below is a preview of future capability, product, network and enterprise services coming soon:



In-flight

- Global Satellite Connection
- Geographical information: Real-time location, Speed, Altitude, Heading
- Emergency alerting
- Real-time Exceedance alerting
- Geofence and flight planning
- Chat messaging
- Push-to-talk
- Voice communications through smart phone applications
- o Live Video and in-cabin Imagery







Operational Command

- Situational awareness C2
- Planning application
- Video and imagery
- Push-to-Talk all informed communication
- Flight exceedance alerting
- Flight analysis for air safety

G6 CERTUS 100 Terminal



*** KEY FEATURES**

- √ 88/88 kbps Satellite Terminal
- ✓ All in one
- Truly Global
- ✓ STCs and MilSpec components
- ✓ Encryption
- ✓ Integrated Iridium and GPS antenna
- ✓ Multiple interfaces
- ✓ Backup power

- ✓ Background IP
- Streaming video
- ✓ Voice, VOIP & PTT
- ✓ Real-time image, health monitoring, telemetry and exceedances
- Automated Flight Following
- Enhanced aerial firefighting

SPECIFICATIONS



Iridium CERTUS CST 88/88kbps



W 14.7 cm (5.8") x L 22.6 cm (8.9") x H 7.8 cm (3.1")



350 g (0.77 lbs) excludes any optional mounting bracket.



POWER

9V - 32VDC wide range 2A



ENVIRONMENTAL



Operating Temperature:

-40 Deg C to +71 Deg C Storage Temperature: -40 Deg C to +90 Deg C



SENSORS

Altimeter, 3 Axis Accelerometer, 3 Axis Gyro, 3 Axis Magnetometer, Temperature



SAND AND DUST PROOF AT

+55 Deg C and ambient



CONNECTORS

13 Pin or 37 Pin Amphenol aerospace circular connector



INTERFACE

WiFi, RS232 Bluetooth 4, 2 Ethernet, 9 digital inputs, 2 digital outputs, 5 analog inputs, analog audio I/O



ALTITUDE

Up to 25,000 Feet



Up to 95% at +55 Deg C



48-hour continuous exposure



ANTENNAS

Built in Iridium CERTUS




INGRESS PROTECTION CODE



FLUID SUSCEPTIBILITY Continuous spray of de-icing fluid

CERTUS Network Architecture



CERTUS Network Applications



HAVE NEWS TO SHARE?

GET IN TOUCH



sales@guardianmobility.com







About Us

<u>More than just tracking</u>, at Guardian Mobility, we empower aircraft fleet managers and owner-operators with fundamental operational data to make timely decisions. Our Airtime and Billing as a Service solution are easy to deploy and tailored to fit your specific requirements.

Contact Us

Address:

Guardian Mobility 43 Auriga Drive Ottawa, Ontario, K2E7Y8

Phone Number & Email:

1.613.225.8885

sales@guardianmobility.com

Want to change how you receive these emails?
You can update your preferences or unsubscribe from this list.

Copyright © 2021 Guardian Mobility. All rights reserved.